

INSTALLATION INSTRUCTION FOR FIXTURE 6693

READ AND SAVE THESE INSTRUCTIONS

MOUNTING THE FIXTURE

1. Shut off the power supply at the fuse box or circuit breaker box. Remove the old fixture from wall. Including the old cross bar.
2. Carefully unpack your new fixture and lay out all the parts in a clear area. Take care not to lose any small parts necessary for installation.
3. Position mounting plate [B] to the junction box [A] using the screw [C]. The side of the mounting Plate marked "GND" must face out.
4. Follow the wiring instructions carefully (See Fig.2).
5. Attach back plate [D] to the mounting plate [B] and secure using screw [E]
6. Place glass cup[H] and metal ring[I] on top of socket and secure with metal cup[J].
7. Install the bulb[J] into socket[G].
8. Install the light bulb in accordance with fixture's specifications. **DO NOT EXCEED THE MAXMUM WATTAGE RATING!**
9. Place glass shades [L] on top of metal cup[J].

Wiring (See fig.2)

1. Connect the electrical wires as follows. Connect the black wire from the fixture to the black (HOT) house wire. Connect the white wire from the fixture to the white (Neutral) house wire. Make sure all the wire nuts were secured. You may wrap the connections with electrical tape. If your outlet box has a ground wire (Green or Bare Copper) connect fixture's ground wire to it. Other wise attach the bare copper fixture wire to the green ground screw on the mounting plate.
2. Tuck the wire connections neatly into the wall junction box.




Fig. 1

