

## INSTALLATION INSTRUCTIONS

WE RECOMMEND THAT A QUALIFIED ELECTRICIAN INSTALL THIS FIXTURE. THIS INSTALLATION MEETS ALL APPLICABLE STATE AND LOCAL CODES.

### GENERAL:

1. TO ENSURE THE SUCCESS OF THE INSTALLATION BE SURE TO READ THESE INSTRUCTIONS THOROUGHLY BEFORE STARTING.
2. THIS FIXTURE IS TO BE MOUNTED TO AN APPROVED OUTLET BOX THAT IS DIRECTLY SUPPORTED BY THE BUILDING STRUCTURE.

### CAUTION:

1. TO AVOID ELECTRICAL SHOCK, MAKE SURE THAT THE ELECTRICITY IS SHUT OFF AT THE MAIN PANEL BEFORE WIRING, ALL WIRING MUST BE IN ACCORDANCE WITH STATE AND LOCAL WIRING CODES.

- 1) Carefully remove all parts from package being careful not to damage any components. Please verify that all parts are present before discarding carton and packing materials.
- 2) Put the fixture (10) on a smooth flat surface.
- 3) Screw the finial (12) onto fixture (10).

- 4) Attach the mounting bracket (3) to the outlet box, by using the slotted holes on the mounting bracket (3) and mounting screws (2). Screw the threaded ring (6) off the screw collar loop (4) which is provided.

- 5) Open up one end of "C" loop by turning the small threaded collar (8) and attach one end of the chain (7) to the "C" loop and to the top loop of the ceiling fixture. Make sure to close the collar portion of the "C" loop once you have connected the chain and fixture base together. Carefully feed the supply wire and ground wire up through the chain every three inch. Slide the threaded ring (6) and canopy (5) onto the chain.

- 6) Twist the fixture's ground wire and the outlet box's ground wire together by the wire connector. Connect the neutral(white) fixture wire to the neutral(white) outlet wire. Fasten together with a wire connector (.). Repeat this procedure with the hot(black) wire. Always make sure that no wire strands are left outside of connectors.

- 7) Slide the canopy (5) and the threaded ring (6) up the chain (7) to the screw collar loop (4). Place the canopy (5) over the outlet box, and secure in place by screwing the threaded ring (6) onto the screw collar loop (4).

- 8) Hang the drops (11) on the lamp at last.

04-3357-28972-6H V3021

