

INSTALLATION INSTRUCTION

CAUTION: shut off main electrical supply from the main fuse box / circuit breaker. We recommend that a qualified electrician install this fixture and that installation meet all state & local electrical codes.

Steps:

- 1) Carefully remove all parts from package. Please verify that all parts are present before discarding carton and packing materials.
- 2) Place fixture(12) on a smooth, flat surface, in order to straighten the arms, loosen the nut on the inside of the arm and turn, making sure to tighten the nut afterwards.
- 3) Place metal arm(9) onto the fixture(12) and lock it with ball finial(8) and nut(10).
- 4) Screw poly finial(13) onto the fixture(12).
- 5) Attach the mounting bracket(3) to the outlet box on ceiling with mounting screws(2). Screw threaded ring(6) off the screw collar loop(4).
- 6) Open up one end of "C" loop by turning the small threaded collar(14) and attach one end of the chain(7) to the "C" loop and to the top loop of the ceiling fixture. Make sure to close the collar portion of the "C" loop to secure the chain to the fixture.
- 7) Carefully feed the supply wire and ground wire up through the chain every three inch. Slide the threaded ring(6) and canopy(5) onto the chain. Make any height adjustments, if necessary.
- 8) Twist the fixture's ground wire and the outlet box's ground wire together by the wire connector.
- 9) Connect the neutral(white) fixture wire to the neutral(white) outlet wire. Fasten together with a wire connector (1). Repeat this procedure with the hot(black) wire. Always make sure that no wire strands are left outside of connectors.
- 10) Slide the canopy and the threaded ring up the chain to the screw collar loop. Place the canopy over the outlet box and secure with threaded ring.
- 11) Place screw the light bulbs(11)(not included) into each socket.
- 12) You may now safely turn on the power.

04-3453-7787-68

